



Technical Data

Model	Displacement mL/r (in ³ /r)	(MPa) pressure			(RPM)pressure		Dimension			
		P1	P2	P3	Rated	Max	L(mm)	M(mm)	F (Inlet)	f (Outlet)
CB1S-F1.3*	1.36 (0.0830)	20	25	28	2000	4000	58.8	98.8	SAE port 3/4-16UN	SAE port 9/16-18UN
CB1S-F2*	2.05 (0.1251)						59.8	100.8		
CB1S-F2.7*	2.74 (0.1672)						60.8	102.8		
CB1S-F3.2*	3.42 (0.2087)						61.8	104.8	BSPP port G1/2"	BSPP port G3/8"
CB1S-F4*	4.10 (0.2502)						62.8	106.8		
CB1S-F5*	5.13 (0.3131)						64.8	109.8		
CB1S-F6*	6.16 (0.3759)	65.8	112.8	Metric port M18X1.5		Metric port M14X1.5				
CB1S-F7*	7.52 (0.4589)	18	20	22		3500	67.8	116.8	7/8-14UN G3/4"	3/4-16UN G1/2"
CB1S-F9*	9.23 (0.5633)					3000	70.3	121.8		
CB1S-F10*	10.95 (0.6682)	15	18	20		2500	72.8	126.8		
CB1S-F13*	13.68 (0.8348)				2000	76.8	134.8			

Copyright: Bucher Hydraulics (Wuxi)Co.,Ltd. 编号: 苏ICP备18069474号-1